

# GS R3523 Thumbbutton Barcode Scanner

## Red cross laser aiming ensures precise targeting and efficient scanning

Red cross laser aiming enables precise aiming, speeds up barcode alignment, improves efficiency, and is clearly visible against most backgrounds, making it suitable for complex environments, so it reduces misreading, improves aiming accuracy, and enhances the user experience.

## Excellent scanning range for a wide range of applications

The R3523 offers an industry-leading scanning range, making it ideal for a wide variety of use cases. For instance, it can read 13mil EAN13 barcodes from distances of up to 70 cm—an unmatched performance in its category. This extended range is especially beneficial in retail industries, enabling truly contactless scanning that enhances the overall shopping experience. It helps reduce checkout congestion during peak hours, boosting hourly order processing capacity from 120 to 180 and improving operational efficiency.

## White illumination realizes natural light restoration for clearer reading

The white illumination offers more natural color rendering, which helps in reading colored barcodes or labels. In addition, softer lighting reduces eye strain during prolonged use. What's more, it ensures barcode clarity under various ambient lighting conditions, improving stability.



## Easy Accessibility and Hands-Free Convenience

Wearing the scanner on a lanyard around the neck ensures that it is always within easy reach. This is especially beneficial for tasks that require frequent but not constant scanning, such as in retail or event management. When not in use, the scanner hangs securely around the neck, leaving the user's hands free to perform other tasks.

## The R3523 has full protocol compatibility and cross-platform adaptability

R3523 offers exceptional versatility by supporting the recognition of virtually all 1D and 2D barcodes, whether black-and-white or in color. It is compatible with three transmission protocols: HID, SPP, and BLE, and supports both classic Bluetooth and Bluetooth Low Energy modes. Additionally, in USB mode, it offers both keyboard emulation and virtual serial port options, making it adaptable to a wide range of systems and application interfaces.

## ACCESSORIES



**Bluetooth Dongle**  
GS GDA201



**Battery Charger**  
GS GCR202(8-slot)/203(16-slot)



**Battery Charger**  
GS GCR201(Dual-Slot)



**Armband**  
(AB1800)



**Thumbbutton trigger button + Lanyard**

## PRODUCT SPECIFICATION

Wearable Barcode Scanner GS R3523

### PHYSICAL PARAMETER

Dimensions	64.8mm(L) × 34.6MM(W) × 24.8mm(H)
Weight	37.0g(Scanner body)
Battery Capacity	600mAh
Charging	5V ---1A
Charging Time	120min
Battery Life	21h(scan once in 5 seconds)
Notification	LED, Buzzer, Vibration

### PERFORMANCE CHARACTERISTICS

Optical Resolution	1280 x 800 pixels
Shutter	Global shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±60° from normal Pitch tolerance: ±60° from normal Roll tolerance: 360° from normal
Illumination	White LED
Aiming	Red Cross Laser
Supported Symbolologies	1D: Code39, Code128, Code 39 full ascii, Trioptic Code39, Code 32, UPC-A, UPC-E, UPC-E1, UPC-E+, UPC-A+, EAN8/JAN8, EAN13/JAN13, Bookland EAN/ISBN, MSI, Codabar, Code11, Interleaved 2 of 5, Industrial 2 of 5, Chinese 2 of 5, Matrix 2 of 5, ISBT, GS1 Databar14, GS1 Databar Limited, GS1 Databar Expanded, GS1-128, Code93 2D: PDF417, Micro PDF417, QR Code, DataMatrix, Micro QR, Hanxin, Grid Matrix, Aztec, Maxicode, GS1 QR, GS1 DataMatrix, GS1 Composite(CC-A/CC-B/CC-C)
Interface	USB, Bluetooth
Offline Mode	Support storage of 3839 EAN-13 barcodes

### SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

### BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

### USB

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

### USER ENVIRONMENT

Ambient Light	Max 100,000lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minutes.
Electrostatic Discharge (ESD)	±8kv DC discharge, ±15kv air discharge
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

### DECODE RANGES

3.3 mil Code 39	110.0 - 190.0 MM
5 mil Code 39	80.0 - 310.0 MM
5 mil QR Code	40.0 - 390.0 MM
13 mil EAN13	60.0 - 700.0 MM
10 mil DataMatrix	90.0 - 270.0 MM
6.7 mil PDF417	110.0 - 260.0 MM

# GENERALS SCAN

Generalscan Inc.

Generalscan LLC

Generalscan Electronics GmbH

+1 732 391 7747 

+90 542 478 5873 

+1 732 391 7747

sales@generalscan.cloud 